

UN
#4
10/10/01JC971 U.S. PTO
09/04/01
JC971 U.S. PTO
09/04/01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Express Mail No.: EL627426155US

In re application of: Matti KANTOLA

Group No.:

Serial No.: 0 /

Examiner:

Filed: Herewith

For: COMMUNICATION DEVICES AND METHOD OF COMMUNICATION


Commissioner of Patents and Trademarks
Washington, D.C. 20231

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country : United Kingdom
 Application Number : 0010982.7
 Filing Date : 5 May 2000

WARNING: "When a document that is required by statute to be certified must be filed, a copy, including a photocopy or facsimile transmission of the certification is not acceptable." 37 CFR 1.4(f) (emphasis added.)


 SIGNATURE OF ATTORNEY

Reg. No.: 24,622

Clarence A. Green

Type or print name of attorney

Perman & Green, LLP

Tel. No.: (203) 259-1800

P.O. Address

425 Post Road, Fairfield, CT 06430

Customer No.: 2512

NOTE: The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63.

(Transmittal of Certified Copy [5-4])

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

JC971 U.S. PTO
09/848515



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 3 April 2001

THIS PAGE BLANK (USPTO)



The Patent Office
Cardiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

08MAY00 F534915-1 002825

F01/7700 0.00-0010982.7

101514/KCS/DG

1. Your reference	101514/KCS/DG		
2. Patent application number (The Patent Office will fill in this part)	0010982.7	05 MAY 2000	
3. Full name, address and postcode of the or of each applicant (underline all surnames)	NOKIA MOBILE PHONES LTD KEILALAHIDENTIE 4 02150 ESPOO FINLAND		
Patents ADP number (if you know it)	5711995004		
If the applicant is a corporate body, give the country/state of its incorporation	FINLAND		
4. Title of the invention	COMMUNICATION DEVICES AND METHOD OF COMMUNICATION		
5. Name of your agent (if you have one)	PAGE WHITE & FARRER 54 DOUGHTY STREET LONDON WC1N 2LS UNITED KINGDOM		
Patents ADP number (if you know it)	1255003		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country (if you know it)	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body See note (d))	YES		

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description	11	/
Claim(s)	3	/
Abstract	1	/
Drawing(s)	3	3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents


Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.



Signature

Date

5 May 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

KELDA STYLE, 0171-831 7929

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

5 **COMMUNICATION DEVICES AND METHOD OF COMMUNICATION**

Field of the Invention

10 The present invention relates to communication devices and a method of communication. In particular, but not exclusively, the present invention relates to wireless communications devices and a method of wireless communications.

Background of the Invention

15 It has been proposed to use mobile stations instead of credit cards at a point of sale. In this proposal, it has been suggested that a wireless link be established between the point of sale device and the mobile station. The mobile station may provide the point of sale device with similar information to that provided by a credit card.

20 One problem with this proposal is how to ensure that the correct mobile station is connected to the point of sale device. For example, in a busy supermarket, there may be a large number of point of sale devices and a large number of mobile stations. It is important that the right point of sale device be connected to the right mobile station. Clearly, considerable problems would be caused if the wrong mobile station was connected to the wrong point of sale device. The user of a mobile station could be charged for goods not purchased by the user.

Summary of the Invention

30 It is an aim of embodiments of the present invention to address the above problems.

NC29730

5 According to one aspect of the present invention, there is provided a portable communications device comprising communication means for communicating with a another party, and identification means for separately providing information on said device, said another party being arranged to obtain said information from said identification means and to use said information to establish communication

10 with said communication means.

The identification means may comprise a bar code, a radio frequency tag or a magnetic data carrying arrangement. The bar code may be arranged on the exterior of the communications device or may be displayed on a display of the

15 communications device. The magnetic data carrying arrangement may comprise a magnetic strip.

The information provided by said identification means may comprise one or more of the following: identity of the device; address of the device when the

20 communication means are used and identity of the user.

The third party may be one of the following devices: point of sale device; ticket sale device; and information kiosk.

25 The link with the another party may be a wireless link. The wireless link may be a high frequency link, for example of the order of giga Hertz. The wireless link may be a Bluetooth link. Alternatively, the wireless link may be an infra red link. The communications device is preferably a mobile telephone.

30 According to a second aspect of the present invention, there is provided a communications device comprising communication means for communicating with a portable party, and identification means for separately providing information on said device, said portable party being arranged to obtain said information from

NC29730

5 said identification means and to use said information to establish communication with said communication means.

According to a third aspect of the present invention, there is provided a method of establishing a communications connection between a portable communications 10 device and another party, said method comprising one of said another party and said portable communications device obtaining information from the other of said another party and said portable communications device; and using said information to separately establish communications between said another party and said communications device.

15

Brief Description of Drawings

For a better understanding of the present invention and as to how the same may be carried into effect, reference will now be made by way of example only to the 20 accompanying drawings in which:-

Figure 1 shows a typical cellular telecommunications network;

Figure 2 shows a block diagram of an embodiment of the present invention;

Figure 3 shows the structure of the mobile station of Figure 2;

25 Figure 4 shows a first embodiment of a mobile station which can be used in the arrangement of Figure 2;

Figure 5 shows a second embodiment of a mobile station which can be used in the arrangement of Figure 2;

Figure 6 shows a third embodiment of a mobile station which can be used in the 30 arrangement of Figure 2; and

Figure 7 shows a fourth embodiment of a mobile station which can be used in the arrangement of Figure 2.

Detailed Description of Embodiments of the Invention

NC29730

5

Reference is made to Figure 1 which shows a typical cellular telecommunications network. The area covered by the network 2 is divided into a plurality of cells 4. Each cell 4 is served by a base transceiver station 6. Each base transceiver station 6 is arranged to communicate with mobile stations 8 in the cell associated 10 with that base transceiver station 6.

The cellular network 2 can use any suitable method of communication. Known methods of communication include those based on time division multiple access, frequency division multiple access and spread spectrum techniques such as code 15 division multiple access. Hybrids of two or more of these access techniques can also be used. In the following description, the mobile station is described as operating in accordance with the UMTS (Universal Mobile Telephone System) standard, which uses code division multiple access. However, the mobile station can operate in accordance with any other suitable standard, for example GSM 20 (Global System for Mobile Communications). GSM uses a time/frequency division multiple access technique.

Reference will now be made to Figure 2 which shows a block diagram of an embodiment of the present invention. Shown in Figure 2 is a service access point 25. The service access point, as will be discussed in more detail later, may be a point of sale device, a ticket gate, an information kiosk or any other suitable service access point. The service access point can be a communication device. The communication device providing the service access point may be arranged to communicate with entities other than the closest mobile station using wired or 30 wireless technologies. Alternatively the communication device may be arranged to communicate only with the closest mobile station. The service access point may be fixed or mobile.

NC29730

5 The service access point 10 has an antenna 12. The antenna 12 is arranged to receive signals from a mobile station. The received signals are passed to a wireless link 14. The wireless link processes the received signals and puts the received data into a format which can be used by the main part 16 of the service access point. The wireless link may convert the received signal to a base band
10 frequency and may carry out decoding and demodulation, as is well known.

The antenna 12 is also arranged to transmit signals to a mobile station. The wireless link 14 receives the data to be transmitted and puts it into a format suitable for transmission. The wireless link 14 may up convert the signals, encode
15 and modulate the data before passing it to the antenna 12 for transmission.

The service access point 10 also comprises a reader 18. The reader 18 is arranged to read information provided by a mobile station 8. This will be described in more detail hereinafter. Figure 2 illustrates how embodiments of the
20 invention are able to overcome the difficulties described earlier. In the arrangement shown in Figure 2, four mobile stations 8a-d are provided. Each of these four mobile stations is reasonably close to the service access point. In the embodiment of the invention, it is desired to establish a connection between the first mobile station 8a and the service access point. It is extremely
25 disadvantageous if, by mistake, a connection were to be established with any of the other three mobile stations 8b to 8d.

The structure of the mobile station 8 is shown in Figure 3. The mobile station 8 has a first antenna 20 and a second antenna 22. The first antenna 20 is connected to a UMTS transceiver 24. The UMTS transceiver 24 is arranged to receive signals from the antenna 20 at a UMTS frequency. The UMTS transceiver 24 decodes the signals, demodulates them and also reduces them to the base band frequency. The output of the UMTS transceiver 24 thus consists of a stream
30 of data. That stream of data may require further processing by the processor 26.

NC29730

5

The UMTS transceiver also receives data from the processor 26 which is to be transmitted by the mobile station. The UMTS transceiver 24 encodes, modulates and up converts the signal to the radio frequency which is to be used. The radio frequency signal is then transmitted by the antenna 20.

10

The second antenna 22 is connected to a Bluetooth transceiver. Bluetooth is a proposed new standard that uses relatively low power radio frequency signals. The frequency may be in the GHz range. This is quite different to the UMTS frequencies. For this reason, separate antennas 20 and 22 are usually provided 15 for the two different types of signal. The Bluetooth transceiver 28 receives Bluetooth frequency signals from the second antenna 22 and decodes, demodulates and down converts those signals. The data output by the Bluetooth transceiver 28 is input to the processor 26. The processor 26 is also arranged to provide data to the Bluetooth transceiver 28 which is to be transmitted by the 20 Bluetooth antenna 22. This data is up converted to the Bluetooth frequency, modulated and encoded before being transmitted by the second antenna 22.

The mobile station 8 also has a display 30. The display is controlled by the processor 26 and provides information for the user. A keypad 32 is provided to 25 allow the user to input numbers and other information. The information input via the keypad 32 is input to the processor 26 which may be controlled in accordance with the input information. The mobile station has a speaker 34. This is controlled by the processor 26 and outputs audio signals which can be heard by the user. A microphone 36 is provided to pick up the user's voice. The microphone signals 30 are input to the processor 26 which converts the signals into a format suitable for output to the UMTS transceiver 24.

Referring back to Figure 2, the mobile station is provided with some form of identification. When the mobile station is moved close to the reader 18, the

NC29730

5 identification of the mobile station 8 is read. The information included in the identification is sufficient to allow a Bluetooth connection to be established between the service access point 10 and the mobile station 8a. The reader has a very short range and is thus only able to obtain the necessary information from the mobile station 8a when the mobile station is very close to the reader 18. The 10 reader 18 would not be able to read the identification information included on mobile stations 8b to 8d. This means that it can be ensured that the connection to the right mobile station is established.

15 The information included in the identification can include any suitable information to allow the connection to be established. In preferred embodiments of the present invention, the identification includes a unique device address for the mobile station. This is effectively the Bluetooth address of the mobile station. This identity can be regarded as being similar to the telephone number of the mobile station. However, the UMTS telephone number will be different from the Bluetooth 20 address. It is the Bluetooth number that is included in the identification information.

Reference will now be made to Figures 4 to 7, which show various examples of how the identity information can be provided.

25

Reference is first made to Figure 4 which shows a first mobile station 100. The mobile station 100 is as shown in Figure 3 and additionally comprises a bar code 102. The bar code 102 is provided on the outer surface of the casing. In the arrangement shown in Figure 4, the bar code is provided on the front of the 30 mobile station 100, below the key pad 32 which in turn is below the display 30. However, the bar code 102 can be provided on any other suitable part of the casing. For example, the bar code may be provided on the back of the device or along any one of the four sides. The bar code may even be provided along the side of the antenna.

NC29730

5

The reader 18 would, in this case, be a bar code reader and would read the bar code 102. The bar code reader 18 would be able to read the unique address contained in the bar code 102. Using that information, the service access point 10 is able to establish a connection with the Bluetooth transceiver 28 of the mobile 10 station.

10

Reference is now made to Figure 5 which shows a mobile station 104 which is modified as compared to the mobile station of Figure 4. The identification takes the form of a bar code 102 which is displayed on the display 30. The reader 18 15 again would be a bar code reader and would read the bar code on the display 30.

15

This latter arrangement has the advantage in that the address of the mobile station can easily be changed without having to replace a bar code on the external cover of the mobile station.

20

Reference is made to Figure 6 which shows an alternative mobile station 106 embodying the present invention. The identification is provided by a radio frequency tag 108. These tags are well known and generally comprise an integrated circuit surrounded by an antenna element. The integrated circuit 25 includes the identity of the mobile station and in particular, its Bluetooth address. The integrated circuit comprises a transponder chip. The reader 18 provides a radio frequency interrogation signal. The frequency of the interrogation signal is selected so that it does not interfere with either the Bluetooth frequencies or the UMTS frequencies. The interrogation signal produces a magnetic flux field that is 30 magnetically coupled to the antenna to energise the latter and to provide power for the transponder integrated circuit. Accordingly, no battery or power supply is required for the radio frequency tag. When the antenna has been energised, the transponder circuitry assembles an identification code signal which includes the Bluetooth address of the mobile station. This signal is fed to the antenna which

NC29730

5 causes the antenna to transmit an information signal which is received by the reader 18. The reader is thus able to obtain the required information.

It should be appreciated that any alternative embodiment of the radio frequency tag can be used in alternative embodiments of the present invention. The radio 10 frequency tag can be incorporated on an exterior surface of the mobile station. However, in preferred embodiments of the present invention, the radio frequency tag can be provided inside the casing as the reader will be able to interrogate the tag through the casing.

15 Reference is made to Figure 7 which shows a fourth embodiment of the present invention. The mobile station 114 is provided with a magnetic strip 116. The reader 18 is thus arranged to read the magnetic strip. It should be appreciated that in alternative embodiments of the present invention, the information can be carried by other forms of magnetic carrier.

20 In the embodiments of the invention described, the identification is provided on the mobile station. However, it is possible in certain embodiments of the present invention, that the reading apparatus be provided on the mobile station and the identification be provided at the service access point. In the latter case, 25 communications would be established by the mobile station. In the embodiments described earlier, the communication between the Bluetooth transceiver of the mobile station and the service access point is initiated by the service access point.

30 The preferred embodiments of the present invention have been described as using a Bluetooth link. However, it should be appreciated that any other suitable radio frequency can be used. For example, infrared frequencies may be used. Preferred embodiments of the present invention use a short range connection

NC29730

5 between the mobile station and the service access point. However, this may not be required in certain embodiments of the present invention.

10 Embodiments of the present invention have a number of different applications. In one embodiment, the mobile station is used to make a transaction with and effectively acts as a credit card, a debit card or an electronic purse. Credit card information for money transfer is done using the Bluetooth connection link which is established between the service access point and the mobile station.

15 Embodiments of the present invention can for example be used at ticket gates. The mobile station includes a ticket to go to a film, concert, sports match or the like. The Bluetooth connection is established between the mobile station and the ticket gate using the identification information. The confirmation of the ticket details are then provided to the ticket gate from the mobile station via the Bluetooth link.

20 Embodiments of the invention can be used to obtain information from an information station. The link is established and the information is exchanged using the Bluetooth connection. For example, the user can obtain train times etc from the information kiosk.

25 In an alternative embodiment of the present invention, the mobile station can be used to communicate with an automatic teller machine ATM to complete financial operations such as the loading of cash to an electronic purse, the withdrawal of cash or the like. The secure communication link between the station and the ATM is established with the ATM reading the address of the mobile station from its bar code or the like.

30 In some embodiments of the present invention, the mobile station may be arranged to act sole as a credit card or the like. In that case the UMTS circuitry

NC29730

5 can be omitted. The mobile station may thus include only the Bluetooth related circuitry. The display, keypad, speaker and/or microphone may therefore be omitted.

10 The described embodiments of the present invention have described a technique for establishing a connection between a service access point and a mobile station. It should be appreciated that embodiments of the present invention may be used to provide communication between any two or more communication devices. For example, embodiments of the present invention can be used to establish a connection between two or more mobile stations.

15 In the preferred embodiments of the present invention, the mobile station may be replaced by any suitable communication device. It should be appreciated that in some embodiments of the invention, the communication capabilities of the communication device and/or the service access point may be very limited. In 20 alternative embodiments of the present invention, the communication capabilities of the communication device and/or the service access point may be more extensive.

25

NC29730

5 CLAIMS

1. A portable communications device comprising communication means for communicating with another party, and identification means for separately providing information on said device, said another party being arranged to obtain said information from said identification means and to use said information to establish communication with said communication means.
10
2. A portable communications device as claimed in claim 1, wherein said identification means comprises a bar code.
15
3. A portable communications device as claimed in claim 2, wherein the bar code is arranged on the exterior of the communications device.
20
4. A portable communications device as claimed in claim 2, wherein the bar code is arranged to be displayed on a display of the communications device.
25
5. A portable communications device as claimed in claim 1, wherein said identification means comprises a radio frequency tag.
30
6. A portable communications device as claimed in claim 1, wherein said identification means comprises a magnetic data carrying arrangement.
7. A portable communications device as claimed in claim 6, wherein said magnetic data carrying arrangement comprises a magnetic strip.
8. A portable communications device as claimed in any preceding claim, wherein said information provided by said identification means comprises one or more of the following:

NC29730

5 Identity of the device; address of the device when the communication means are used; and identity of the user.

9. A portable communications device as claimed in any preceding claim, wherein said another party is one of the following devices:

10 point of sale device; ticket gate device; and information kiosk.

10. A portable communications device as claimed in any preceding claim, wherein said link with said third party is a wireless link.

15 11. A portable communications device as claimed in claim 10, wherein said wireless link is a high frequency link.

12. A portable communications device as claimed in claim 11, wherein said high frequency link is of the order of giga Hertz.

20 13. A portable communications device as claimed in claim 12, wherein said wireless link is a Bluetooth link.

14. A portable communications device as claimed in claim 10, wherein the
25 wireless link is an infrared link.

15. A portable communications device as claimed in any preceding claim, wherein said communications device is a mobile telephone.

30 16. A communications device comprising communication means for communicating with a portable party, and identification means for separately providing information on said device, said portable party being arranged to obtain said information from said identification means and to use said information to establish communication with said communication means.

NC29730

5

17. A method of establishing a communications connection between a portable communications device and another party, said method comprising:
one of said another party and said portable communications device obtaining information from the other of said another party and said portable communications device; and

10 using said information to separately establish communications between said another party and said communications device.

18. A method as claimed in claim 17, wherein said another party comprises a
15 portable communications device.

19. A method as claimed in claim 17 or 18, wherein at least one of said another party and said portable communications device comprises a mobile telephone.

20

ABSTRACT

COMMUNICATION DEVICES AND METHOD OF COMMUNICATION

A portable communications device comprising communication means for communicating with a another party, and identification means for separately 10 providing information on said device, said another party being arranged to obtain said information from said identification means and to use said information to establish communication with said communication means.

THIS PAGE BLANK (U/SPR0)




FIGURE 3




FIGURE 1

THIS PAGE BLANK (USPTO)




FIGURE 2

THIS PAGE BLANK (USPTO)




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7

THIS PAGE BLANK (USPTO)